

Model	REP5000-121	REP5000-241	REP5000-481	REP5000-122	REP5000-242	REP5000-482
Rated power	5000W					
Peak power	10000W					
Input voltage	DC12V	DC24V	DC48V	DC12V	DC24V	DC48V
Output voltage	100VAC or 110VAC or 120VAC±5%			220VAC or 230VAC or 240VAC±5%		
Unload current less	1.2A	0.8A	0.5A	1.2A	0.8A	0.5A
Output frequency	50Hz±0.5Hz or 60Hz±0.5Hz					
Output waveform	Pure Sine Wave					
Waveform distortion	THD < 3%(Linear load)					
USB port	QC3.0		/	QC3.0		/
Max. efficiency	90%	92%	95%	90%	92%	95%
Input voltage range	10-15.5V	20-31V	40-61V	10-15.5V	20-31V	40-61V
Low voltage alarm	10.5±0.5V	21±0.5V	42±1V	10.5±0.5V	21±0.5V	42±1V
Low voltage	10±0.5V	20±0.5V	40±15V	10±0.5V	20±0.5V	40±15V
Over voltage	15.5±0.5V	31±0.5V	61±1V	15.5±0.5V	31±0.5V	61±1V
Low voltage recover	12.3±0.5V	24±0.5V	48±1V	12.3±0.5V	24±0.5V	48±1V
Over voltage recover	14.8V±0.5V	29.5V±0.5V	59V±1V	14.8V±0.5V	29.5V±0.5V	59V±1V
Protection function	Low voltage		Alarm at first, voltage continuously reduce. LED Red light on & shut sown			
	Over voltage		LED Red light on, shut down			
	Over load		LED Red light on, shut down			
	Over temperature		Alarm at first, temprature continuously rise. LED Red light on & shut sown			
	Short circuit		LED Red light on			
	Input reverse polarity		Fuse burn-out			
Working temperature	-10°- +50°					
Storage temperature	-30°- +70°					
Dimension(mm)	475x205x152mm					
Packing(mm)	565x302x240mm					
Net./gross weight(g)	8540/11000G					
QTY/Ctn	1 Pcs					
Meas./Ctn(mm)	565x302x240mm					
Gross weight/Ctn(g)	11000g					
Warranty	2 years					
Configuration	Standard					
Cooling method	Intelligent air cooling					
Custom-made available: Except for the regular DC input voltages: 12V, 24V, 48V, we also could provide customized DC input voltages: DC 36V, DC 60V, DC 72V, DC 84V, DC 96V...						